

System	H100(Head) + T103(Tripod) + SP-6(Floor spreader) + SC-7(Softcase)		
Payload	25kg / 55lb	Tilt angle	±90° (Limited to ±60° with maximum counterbalance)
Weight	12.2kg / 26.8lb	Pan angle	360°
Height	① H: 1910 mm W: 730 mm (※Reference)	Counterbalance	Range : 11.5kg-20kg / 25.5-44lb (CG125mm)
	② H: 790 mm W: 1125 mm (")		System : Continuous
Folded length	③ L: 1005 mm (")	Drag mode	Continuous
Camera plate (Sliding range)	Sliding plate ±50 mm / ±2"	Ball diameter	φ 100 mm
Plate attachment (Screw sliding range)	Type: 3/8-16UNC screw x 2	Section	2STAGE (Material: Aluminum)
	46 mm	Tripod fixation	Fixing lock knob
Spare screw	Type: 3/8-16UNC screw	Spreader	SP-6 (Telescopic, Removable)
	Equipped on the top of the head (beneath sliding plate)	Pan handle	PH-7
		Case material	Nylon

Remarks

Outside diameter of pipe

Upper: φ 24 / Middle: φ 24 / Lower : φ 20

■ Exterior Dimensions (mm)

