

System	RH35(Head) + RT30B(Tripod) + SP-2B(Floor spreader) + RC-30(Carrying case)		
Payload	9kg / 20lb	Tilt angle	+90° / -70° (Limited to ±40° with maximum counterbalance)
Weight	6kg / 13.2lb	Pan angle	360°
Height	① H: 1660 mm W: 710 mm (※Reference)	Counterbalance	Range : 3kg-7.5kg / 6.5-16.5lb (CG100mm)
	② H: 560 mm W: 1105 mm (")		System : Continuous
Folded length	③ L: 855 mm (")	Drag mode	Free plus 3STEP
Camera plate (Sliding range)	Sliding plate ±40 mm / ±1.6"	Ball diameter	∅75 mm
Plate attachment (Screw sliding range)	Type: 1/4-20UNC screw with video pin 52 mm	Section	2STAGE (Material: Aluminum)
Spare screw	Type: 1/4-20UNC, 3/8-16UNC screws	Tripod fixation	Fixing lock knob
	Equipped on the top of the head (beneath sliding plate)	Spreader	SP-2B (Telescopic, Removable)
		Pan handle	PH-4B
		Case material	Nylon

Remarks

※Counter - balance support knob is included in RS-350

Exterior Dimensions (mm)

