

| | | | |
|----------------------------------------|----------------------------------------------------------------------------------------------------------|-----------------|-----------------------------------------------------------|
| System | RH35(Head) + RT30B(Tripod) + BR-2B(Mid-level spreader) + FP-2B(Large rubber feet) + RC-30(Carrying case) | | |
| Payload | 9kg / 20lb | Tilt angle | +90° / -70° (Limited to ±40° with maximum counterbalance) |
| Weight | 5.8kg / 12.8lb | Pan angle | 360° |
| Height | ① H: 1655 mm W: 800 mm (※Reference) | Counterbalance | Range : 3kg-7.5kg / 6.5-16.5lb (CG100mm) |
| | ② H: 810 mm W: 570 mm (") | | System : Continuous |
| Folded length | ③ L: 855 mm (") | Drag mode | Free plus 3STEP |
| Camera plate (Sliding range) | Sliding plate ±40 mm / ±1.6" | Ball diameter | ∅75 mm |
| Plate attachment (Screw sliding range) | Type: 1/4-20UNC screw with video pin | Section | 2STAGE (Material: Aluminum) |
| | 52 mm | Tripod fixation | Fixing lock knob |
| Spare screw | Type: 1/4-20UNC, 3/8-16UNC screws | Spreader | BR-2B (Telescopic, Removable) |
| | Equipped on the top of the head (beneath sliding plate) | Pan handle | PH-4B |
| | | Case material | Nylon |

Remarks

※Counter - balance support knob is included in RS-350M

Exterior Dimensions (mm)

