

Libec
Craftsmanship from Japan



HANDS-FREE MONOPOD

TH-M

TH-M

HANDS-FREE MONOPOD

By stepping on the lock/release foot pedals, conveniently located symmetrically in three sections on the Free-stand Base, you are able to quickly lock/release the monopod during photo and video shoots.

Perfect Lock Feature

When users lock the bottom part of the monopod by stepping on the foot pedal, the ball joint will be locked as well. The pan movement of the head on the monopod is smoother than ever, allowing the users to control the camera's manual focus while panning at the same time when shooting.

Upgraded Head Attachment

The former HFMP monopod can only support equipment with a 3/8" screw hole. However, the new TH-M's head attachment is equipped with both a 1/4" screw and a 3/8" screw.

Improved Rigidity

Advanced head attachment made with new aluminum material to maximize the monopod's rigidity.

Easy to Maintain

The Free-stand Base has been redesigned allowing users to easily remove dirt when necessary.



Dual Size Screw Design for Equipment with 1/4" & 3/8" Screw Holes



Speedy Open / Close Functions



A Sleek Design with Numeric Indicators for Your Preferred Height Settings



Industry Standard Sliding Plates Compatible with Manfrotto, Sachtler



Carrying Bag Included

TH-M

TH-M KIT



TH-M

TH-M KIT

	TH-M	TH-M KIT
Payload	8kg / 17.6lbs (Including head)	4kg / 9lbs
Tilt Angle	—	+90° / -80°
Dual Pan Function Design	—	Pan function on head
Temperature Range	—	-20°C to +60°C / -4°F to +140°F
Weight	1.8kg / 4.0lb	2.7kg / 5.9lb
Height	74.0 to 176.0cm / 29.1 to 69.3"	87.5 to 189.5cm / 34.4 to 74.6"
Section	2 STAGE	2 STAGE
Leg Lock Type	Lock / Release Levers	Lock / Release Levers
Head Attachment Screw	1/4" screw, 3/8" screw	1/4" screw, 3/8" screw
Camera Plate	—	Sliding plate Compatible with Manfrotto and Sachtler heads
Construction Material	Aluminum	Aluminum
Pipe Diameters (upper / mid / low)	34mm / 29.5mm / 25mm	34mm / 29.5mm / 25mm
Monopod Case	Included	Included