



- ★ : Require proper types of adhesive.
- ★a : Two-component adhesive. (Epoxy resin system)
- ★b : Instant adhesive.
- ★c : Thread locking adhesives. (Anaerobic adhesive)
- ※ : Grease that doesn't affect plastic.
- : Grease which is applied before shipment.

Libec ALX S4,S8,S12 SERVICE PARTS

No.	PART No.	DESCRIPTION	Q'TY USED	NOTE
1	ALXS-1	Bearing plate assembly	1	
2	ALXS-2	Bearing plate	1	
3	ALXS-3	Bearing bolt assembly	2	2 Pcs. set (Bolt 2Pcs.+Bearing 2Pcs.)
4	ALXS-4	Bearing	4	2 Pcs. set
5	ALXS-5	Slider body assembly	1	
6	ALXS-6	Brake knob	1	
7	ALXS-7	Slider body	1	With level and friction push-piece assembly.
8	ALXS-8	Friction push-piece assembly	1	
9	ALXS-9	Camera screw (3/8-16UNC)	1	
10	ALXS-10	Bearing shaft assembly	2	Shaft 1Pc.+Bearing 2Pcs.+Bolt 2Pcs.
11	ALXS-11	Leg base assembly	2	With leg base knob 1Pc.
12	ALXS-12	Hexagonal socket cap low head bolt	2	3 Pcs. set
13	ALXS-13	Leg base	2	With leg base knob 1Pc.
14	ALXS-14	Leg base stopper rubber	1	4 Pcs. set
15	ALXS-15	Leg assembly	4	
16	ALXS-16	Leg	4	
17	ALXS-17	Leg lock knob	4	
18	ALXS-18	Leg adjuster	4	
19	ALXS-19	Tripod mount adapter	1	ALX S4,S8
			2	ALX S12
20	ALXS-20	Bowl clamp	1	ALX S4,S8
			2	ALX S12
21	ALXS-21	Protector	1	
22	ALXS-22	Maintenance tool	1	With brush and hexagonal wrench.
23	ALXS-23	Leg base knob	2	With Washer and O-ring.
24	ALXS-24	Slider rail (S4)	1	Rail length : 400mm / 15.5"
25	ALXS-25	Slider rail (S8)	1	Rail length : 800mm / 31.5"
26	ALXS-26	Slider rail (S12)	1	Rail length : 1200mm / 47"
27	ALXS-27	Slider platform	1	