


System	H15 (Head) + QL40C (Tripod) + SP-1B (Floor spreader) + RC-30 (Carrying case)		
Payload	3 kg / 6.6 lb	Tilt angle	+90° / -70°
Weight	5.7 kg / 12.5 lb	Drag mode	Free plus 3 steps
Operating Dimensions	① H : 1680 mm W : 710 mm (※Reference)	Temperature range	-40 °C ~ +60 °C / -40 °F ~ 140 °F
	② H : 550 mm W : 1090 mm (")	Accessory port	1/4" and 3/8" screw holes (head : 1set , tripod : 3sets)
Folded length	③ L : 845 mm (")	Head base	Ball 75 mm
Camera plate	Sliding plate (compatible with Manfrotto and Sachtler)	Carrying handle	Included
	One touch attach and release mechanism	Section	2-Stage
Counterbalance	Range : 0.8 ~ 2.0 kg / 1.7 ~ 4.4 lb (C.G. 55 mm)	Leg lock system	Flip lock
	Perfect Balance	Spreader	SP-1B (Telescopic , Removable)
	Continuous Counterbalance with Illuminated Meter	Case material	Nylon , Polyester , TPE , PE , PP , POM

Remarks

* Includes adjustment tool.

■ Exterior Dimensions (mm)



※ Reference

