

System	LX-ePed column (Electric Pedestal) + SP-2B (Floor spreader)		
Payload	10 kg / 22 lb	Head attachment	100 mm bowl
Weight	11.2 kg / 24.7 lb (excluding controller and AC adapter)	Tripod section	2-Stage
	LX-ePed column : 10.3 kg / 22.7 lb , SP-2B : 0.9 kg / 2 lb	Camera attachment	1/4" and 3/8" screws
Height	① H : 2470 mm / 97.2" (※Reference)	Accessory port	1/4" and 3/8" screw holes x 2
	② H : 955 mm / 37.6" (")	Temperature range	-10°C ~ 40°C / -40°F ~ 104°F , Below RH 90%
Folded length	③ L : φ241 mm × 1005 mm / φ9.4" × 39.6"	Controller cable	LAN Cable : 30 m / 98.4'
Width	W1 : 620 mm / 24.4" , W2 : 710 mm / 28"	Power cable	AC / DC Adapter : 3 m / 9.8'
Elevation	400 mm	Power	AC 100 V ~ 240 V
Raising / Lowering speed	Approx. 14 ~ 40 secs. / movement		Battery-powered (optional)
Continuous operating time	3 minutes		

Remarks

■ Exterior Dimensions (mm)

