

System	LX5 Head + RT30RB (Tripod) + BR-2B (Mid-level spreader) + FP-2B (Large rubber feet) + RC-20 (Carrying case)		
Payload	5 kg / 11.0 lb	Counterbalance	FIX
Weight	5.3 kg / 11.7 lb	Drag mode	FIX
Height	① H : 1655 mm W : 800 mm (※ Reference)	Temperature range	-20 °C ~ +60 °C / -4 °F ~ +140 °F
	② H : 810 mm W : 570 mm (")	Ball diameter	ø75 mm
Folded length	③ L : 855 mm (")	Section	2-Stage (Material : Aluminum)
Camera plate	Sliding plate	Tripod fixation	Fixing lock knob
(Sliding range)	±40 mm / ±1.6"	Spreader	BR-2B (Telescopic , Removable)
Plate attachment	1/4-20UNC screw + video pin	Pan handle	PH-5B
(Screw sliding range)	76 mm / 3"	Accessory port	1/4" and 3/8" screw holes (3 sets)
Tilt angle	+90° / -80°	Carrying handle	Included
Pan angle	360°	Case material	Nylon

Remarks

※ Hex Key Wrench (for Carrying handle attachment / detachment) is included.

Exterior Dimensions (mm)

