

<b>System</b>	H65B ( Head + dual pan handle) + RT50B ( Tripod ) + DL-3RB ( Dolly )		
<b>Payload</b>	16 kg / 35.3 lb	<b>Tilt angle</b>	+85° / -65°
<b>Weight</b>	10.9 kg / 24.0 lb	<b>Pan angle</b>	360°
<b>Height</b>	Max 1875mm / 73.81"	<b>Counterbalance</b>	FIX
	Min 920mm / 36.22"	<b>Drag mode</b>	Both tilt and pan 2 STEP
<b>Camera plate (Sliding range)</b>	Sliding plate	<b>Temperature range</b>	-20 °C ~ +60 °C / -4 °F ~ +140 °F
	±50 mm / ±2"	<b>Ball diameter</b>	φ 100 mm
<b>Plate attachment (Screw sliding range)</b>	3/8-16UNC screw	<b>Section</b>	2STAGE ( Material : Aluminum )
	100 mm / 4"	<b>Tripod fixation</b>	Fixing lock knob
<b>Spare screw</b>	3/8-16UNC screw	<b>Dolly</b>	DL-3RB
	Equipped on the top of the head ( beneath sliding plate )	<b>Pan handle</b>	PH-8B x 2

### Remarks

### ■ Exterior Dimensions (mm)

