

System	NH10 (Head) + RT20C (Tripod) + SP-1B (Floor spreader) + RC-30 (Carrying case)		
Payload	4 kg / 8.8 lb	Tilt angle	+90° / -70°
Weight	4.1 kg / 9.0 lb	Pan angle	360°
Height	① H : 1675 mm W : 710 mm (※Reference)	Counterbalance	Loading range : 0 ~ 2.5 kg / 0 ~ 5.5 lb (C.G. 55 mm)
	② H : 525 mm W : 1090 mm (")		System: free plus 5 steps
Folded length	③ L : 835 mm (")	Drag mode	Free plus 3 steps
Camera plate (Sliding range)	Sliding plate	Drag mechanism	Metal lamination unit
	Compatible with Manfrotto and Sachtler	Temperature range	-40 °C ~ +60 °C / -40°F ~ +140°F
Plate attachment (Screw sliding range)	1/4-20UNC (with video boss)	Head base	Ball 75 mm / Flat base
	68 mm / 2.6"	Section	2STAGE (Material : Carbon)
Spare screw	1/4-20UNC × 1 , 3/8-16UNC × 1	Leg lock system	Fixing lock knob
	Equipped on the top of the head (beneath sliding plate)	Spreader	SP-1B (Telescopic , Removable)
Accessory port	1/4-20UNC × 1 , 3/8-16UNC × 1	Pan handle	Dedicated pan handle
	Left side of head : Screw hole 1/4" × 1 , 3/8" × 1	Case material	Nylon , Polyester , TPE , PE , PP , POM

Remarks

Exterior Dimensions (mm)

