

<b>System</b>	NH10 ( Head ) + RT20C ( Tripod ) + BR-2B ( Mid-level spreader ) + FP-1B ( Large rubber feet ) + RC-20 ( Carrying case )		
<b>Payload</b>	4 kg / 8.8 lb	<b>Tilt angle</b>	+90° / -70°
<b>Weight</b>	3.8 kg / 8.3 lb	<b>Pan angle</b>	360°
<b>Height</b>	① H : 1670 mm W : 780 mm ( ※Reference )	<b>Counterbalance</b>	Loading range : 0 ~ 2.5 kg / 0 ~ 5.5 lb ( C.G. 55 mm )
	② H : 800 mm W : 575 mm ( " )		System : 0 + 5 STEP
<b>Folded length</b>	③ L : 835 mm ( " )	<b>Drag mode</b>	Both tilt and pan 0 + 3 STEP
<b>Camera plate</b> (Sliding range)	Sliding plate	<b>Drag mechanism</b>	Metal lamination unit
	Compatible with Manfrotto and Sachtler	<b>Head base</b>	Ball 75 mm / Flat base
<b>Plate attachment</b> (Screw sliding range)	1/4-20UNC + Video pin	<b>Accessory port</b>	Left side of head : Screw hole 1/4" × 1, 3/8" × 1
<b>Spare screw</b>	68 mm / 2.6"	<b>Section</b>	2STAGE ( Material : Carbon )
	1/4-20UNC × 1, 3/8-16UNC × 1	<b>Tripod fixation</b>	Fixing lock knob
<b>Temperature range</b>	Equipped on the top of the head ( beneath sliding plate )	<b>Spreader</b>	BR-2B ( Telescopic , Removable )
	-40 °C ~ +60 °C / -40°F ~ +140°F	<b>Pan handle</b>	Dedicated pan handle
		<b>Case material</b>	Nylon , Polyester , TPE , PE , PP , POM

### Remarks

### ■ Exterior Dimensions (mm)

