

System	NH30 (Head)		
Payload	10 kg / 22.0 lb	Tilt angle	+90° / -70°
Weight	1.8 kg / 4.0 lb	Pan angle	360°
Camera plate (Sliding range)	2 Sliding plates (Standard + Long)	Counterbalance	Loading range : 0 ~ 10 kg / 0 ~ 22 lb (CG 55 mm) System: 0 + 5 STEP
	Compatible with Manfrotto and Sachtler		
Plate attachment (Screw sliding range)	Standard : ±30 mm / ±1.2" , Long : ±85 mm / ±3.3"	Drag mode	Tilt : 0 + 3 STEP Pan : 0 + 3 STEP
	Standard : 1/4-20UNC + Video pin		
Spare screw	Long : 1/4-20UNC × 1 , 3/8-16UNC × 2	Drag mechanism	Metal lamination unit
	Standard : 68 mm / 2.6" , Long : 85 mm / 3.3"		
Bubble level	1/4-20UNC × 1 , 3/8-16UNC × 1	Temperature range	-40 °C ~ +60 °C / -40°F ~ +140°F
	Equipped on the top of the head (beneath sliding plate)		
		Head attachment	Ball 75 mm / Flat base
		Accessory port	Left side of head : Screw hole 1/4" × 1 , 3/8" × 1
		Pan handle	Dedicated pan handle

Remarks

■ Exterior Dimensions (mm)

■ Sliding plates (2 Type)

