

<b>System</b>	GH75 (Head) + P110B (Pedestal system)		
<b>Payload</b>	17 kg / 37.5 lb	<b>Counterbalance</b>	Range : 5.5 ~ 14 kg / 12 ~ 31 lb (C.G. 125 mm)
<b>Weight</b>	21 kg / 46.2 lb		Perfect Balance
<b>Height</b>	Max : 1750 mm / 68.9" Min : 1000 mm / 39.4"		Continuous counterbalance with meter
<b>Operating Dimensions</b>	W1 : 920 mm / 36.2" W2 : 1055 mm / 41.5" (※ Reference)	<b>Temperature range</b>	-40 °C ~ +60 °C / -40 °F ~ +140 °F
<b>Column section</b>	2-Stage	<b>Head attachment</b>	100 mm bowl
<b>Column stroke</b>	750 mm / 29.5" (Upper : 380 mm / 15", Middle : 370 mm / 14.6")	<b>Camera plate</b>	Sliding plate
	Upper column : air pressure , Middle column : manual	(Sliding range)	±55 mm / ±2.2"
<b>Tilt angle</b>	+90° / -70° (Limited to ±40° with max counterbalance)	<b>Accessory port</b>	1/4" and 3/8" screw holes (Head : 1set)
<b>Drag mode</b>	Free plus 7 steps	<b>Pan handle</b>	PH-8B x 2

**Remarks**

■ Exterior Dimensions (mm)

