

System	GH85 (Head) + P110S (Pedestal system)		
Payload	25 kg / 55 lb	Counterbalance	Range : 9 ~ 20 kg / 20 ~ 44 lb (C.G. 125 mm)
Weight	22.2 kg / 48.8 lb		Perfect Balance
Height	Max : 1735 mm / 68.3 lb Min : 985 mm / 38.8 lb		Continuous counterbalance with meter
Operating Dimensions	W1 : 980 mm / 38.6" W2 : 1115 mm / 43.9" (※ Reference)	Temperature range	-40 °C ~ +60 °C / -40 °F ~ +140 °F
Column section	2-Stage	Head attachment	100 mm bowl
Column stroke	750 mm / 29.5" (Upper : 380 mm / 15", Middle : 370 mm / 14.6")	Camera plate	2 Sliding plates (Standard , Long)
	Upper column : air pressure , Middle column : manual	(Sliding range)	Standard : ±55 mm / ±2.2" , Long : ±85 mm / ±3.3"
Tilt angle	+90° / -70° (Limited to ±40° with max counterbalance)	Accessory port	1/4" and 3/8" screw holes (Head : 1set)
Drag mode	Free plus 7 steps	Pan handle	PH-8B x 2

Remarks

■ Exterior Dimensions (mm)

