

<b>System</b>	RHP75 ( Head ) + PH-8B ( Pan handle ) × 2 + P110B ( Pedestal system )		
<b>Payload</b>	17 kg / 37.5 lb	<b>Tilt angle</b>	+90° / -70° ( Limited to ±40° with maximum counterbalance )
<b>Weight</b>	20.8 kg / 45.8 lb	<b>Pan angle</b>	360°
<b>Height</b>	Max : 1760 mm / 69.3"	<b>Counterbalance</b>	Range : 5.5~14 kg / 12~31 lb ( C.G. 125 mm )
	Min : 1010 mm / 39.8"		System : Continuous
<b>Camera plate (Sliding range)</b>	Sliding plate	<b>Drag mode</b>	7 STEP
	±55 mm / ±2.2"	<b>Ball diameter</b>	∅100 mm
<b>Plate attachment (Screw sliding range)</b>	3/8-16UNC × 2	<b>Column section</b>	2 STAGE
	102 mm / 4"	<b>Column stroke</b>	750 mm / 29.5" ( Upper : 380 mm / 14.9" , Middle : 370 mm / 14.5" )
<b>Spare screw</b>	3/8-16UNC × 1		Upper column : air pressure , Mid column : manual
	Equipped on the head ( Behind the platform of sliding plate )		<b>Pan handle</b>

### Remarks

### ■ Exterior Dimensions (mm)

#### ■ RHP75

