

System	RHP85 (Head) + PH-8B (Pan handle) × 2 + P110B (Pedestal system)		
Payload	25 kg / 55.0 lb	Tilt angle	+90° / -70° (Limited to ±40° with maximum counterbalance)
Weight	20.9 kg / 46.0 lb	Pan angle	360°
Height	Max : 1760 mm / 69.3"	Counterbalance	Range : 9~20 kg / 20~44 lb (C.G. 125 mm)
	Min : 1010 mm / 39.8"		System : Continuous
Camera plate (Sliding range)	2 Sliding plates (Standard + Long)	Drag mode	7 STEP
	Standard : ±55 mm / ±2.2" , Long : ±85 mm / ±3.3"	Ball diameter	∅100 mm
Plate attachment (Screw sliding range)	3/8-16UNC × 2	Column section	2 STAGE
	Standard : 102 mm / 4" , Long : 95 mm / 3.7"	Column stroke	750 mm / 29.5" (Upper : 380 mm / 14.9" , Middle : 370 mm / 14.5")
Spare screw	3/8-16UNC × 1		Upper column : air pressure , Mid column : manual
	Equipped on the head (Behind the platform of sliding plate)	Pan handle	PH-8B × 2

Remarks

■ Exterior Dimensions (mm)

■ RHP85

