

System	H25 (Head)		
Payload	5 kg / 11.0 lb	Tilt angle	+90° / -70° (Limited to ±50° with maximum counterbalance)
Weight	2.8 kg / 6.2 lb	Pan angle	360°
Camera plate (Sliding range)	Sliding plate (compatible with Manfrotto and Sachtler)	Counterbalance	Range : 1.7 ~ 4.5 kg / 3.7 ~ 9.9 lb (C.G. 100 mm)
	One touch attach and release mechanism		Perfect Balance
	±30 mm / ±1.2"		Continuous Counterbalance with Illuminated Meter
Plate attachment (Screw sliding range)	1/4-20UNC (with video boss)	Drag mode	Free plus 3 steps
	68 mm / 2.6"	Drag system	Multilayered Metal Structure
Spare screw	1/4-20UNC × 1 , 3/8-16UNC × 1	Temperature range	-40 °C ~ +60 °C / -40°F ~ +140°F
	Equipped on the top of the head (beneath sliding plate)	Head base	Ball 75 mm / Flat base with 3/8" female thread
Bubble level	Illuminated	Accessory port	Screw hole 1/4" × 1 , 3/8" × 1
		Pan handle	PH-6B (Telescopic)

Remarks

■ Exterior Dimensions (mm)

