

System	NH10 (Head) + RT20C (Tripod) + SP-1B (Floor spreader) + RC-20 (Carrying case)		
Payload	4 kg / 8.8 lb	Tilt angle	+90° / -70°
Weight	4.1 kg / 9.0 lb	Pan angle	360°
Height	① H : 1680 mm W : 710 mm (※Reference)	Counterbalance	Loading range : 0 ~ 2.5 kg / 0 ~ 5.5 lb (C.G. 55 mm)
	② H : 530 mm W : 1090 mm (")		System : 0 + 5 STEP
Folded length	③ L : 835 mm (")	Drag mode	Both tilt and pan 0 + 3 STEP
Camera plate (Sliding range)	Sliding plate	Drag mechanism	Metal lamination unit
	Compatible with Manfrotto and Sachtler	Head base	Ball 75 mm / Flat base
Plate attachment (Screw sliding range)	1/4-20UNC + Video pin	Accessory port	Left side of head : Screw hole 1/4" × 1, 3/8" × 1
Spare screw	68 mm / 2.6"	Section	2STAGE (Material : Carbon)
	1/4-20UNC × 1, 3/8-16UNC × 1	Tripod fixation	Fixing lock knob
Temperature range	Equipped on the top of the head (beneath sliding plate)	Spreader	SP-1B (Telescopic , Removable)
	-40 °C ~ +60 °C / -40°F ~ +140°F	Pan handle	Dedicated pan handle
		Case material	Nylon , Polyester , TPE , PE , PP , POM

Remarks

■ Exterior Dimensions (mm)

